



illumination design  
SINCE 1972



# TECHNICAL SHEETS



illumination design  
SINCE 1972



# TECHNICAL SHEETS



MATERIALI / MATERIALS	
Struttura / Frame	Ferro - Acciaio - Ottone / Iron - Steel - Brass
Vetro / Glass	Pirex (vetro borosilicato temperato) / Pirex (tempered borosilicate glass)

DATI TECNICI / TECHNICAL DATA		
INFO	EUROPE	USA
Prodotto / Product	Lampadario / Chandelier	Lampadario / Chandelier
Installazione / Installation	Soffitto / Ceiling	Soffitto / Ceiling
Diametro / Diameter	74 cm.	24,13"
Altezza / Height	87 cm.	34,25"
Lunghezza asta / Rod lenght	60 cm.	23,62"
Lunghezza vetro / Glass height	25 cm.	9,84"
Rosone / Canopy	Ø 15 cm. - h.5 cm.	Ø 5,90" - h.1,96"

SPECIFICHE ELETTRICHE / ELECTRICAL SPECIFICATIONS		
INFO	EUROPE	USA
Alimentazione / Power Supply	220-240V - 50/60Hz	100-120V - 50/60Hz
Specifiche lampade/Bulbs specifications	30x0,8W chip led 4000K (incl. / incl.)	30x0,8W chip led 4000K (incl. / incl.)
Wattaggio massimo / Max wattage	24W (4050 lumen)	24W (4050 lumen)
Tensione led / Led voltage	24VDC (driver incl. / driver incl.)	24VDC (driver incl. / driver incl.)
Dimmerabilità / Dimmability	Su richiesta / On request	Su richiesta / On request

OPZIONE DECORI STANDARD / STANDARD FINISHING OPTIONS		Opzioni vetri / Glass options
nickel / nickel	oro shadow / shadow gold	 Pirex sabbato con sfumatura trasparente Frosted pyrex with transparent shadow
cromo / chrome	placcato oro / gold plated	
nickel satinato / satin nickel	ottone satinato / satin brass	
nickel nero / black nickel	brunito spazzolato / brushed bronze	
placcato rame / copper plated		

PESO E VOLUME / WEIGHT AND VOLUME		
 Peso Netto / Net weight Kg.7,00	 Volume M3 0,540	 Peso Lordo / Gross weight Kg.13,00

--- MADE IN ITALY ---